

In the Claims:

Please replace claims 1, 4-8, 10, 11, 13-16, 20, 25 and 31, all as shown below.

1. (Currently Amended): A method, comprising:
providing a camera array, the camera array including a plurality of cameras;
providing a set of camera offset values for the camera array;
synchronously capturing a set of images from [a] the camera array;
selecting pixels from at least one image of said set of images;
applying a bilinear transformation to the selected pixels to transform the selected pixels from a coordinate system of the at least one image to a common coordinate system of a composite image;
wherein applying a bilinear transformation includes using the set of camera offset values.
- 2-3 (Cancelled)
4. (Currently Amended): The method according to claim 1, wherein ~~said step of selecting pixels comprises:~~ includes identifying ~~a set of~~ contiguous patches in ~~each of~~ said set of images.
5. (Currently Amended): The method according to claim 4, wherein ~~said step of identifying contiguous patches, comprises:~~ includes identifying ~~regions in each image~~ pixels from the contiguous patches having registration points in common with said composite image.
6. (Currently Amended): The method according to claim 4, further comprising:
combining patches from different images of said set of images pixels from the contiguous patches having ~~a same set of~~ substantially similar registration points into a ~~same corresponding common~~ location of said composite image.
7. (Currently Amended): The method according to claim 6, wherein ~~said step of combining pixels from the contiguous patches includes~~ comprises the step of: cross-fading ~~patches from different images of said set of images~~ pixels having substantially similar registration points having ~~a same set of~~ substantially similar registration points into a ~~same corresponding~~ the common location of said composite image.

8. (Currently Amended): The method according to claim 6, wherein ~~said step of combining pixels from the contiguous patches~~ includes at least one of cross-fading, blurring, averaging, and other image effects to seamlessly combine said ~~patches pixels~~ from different ~~images patches~~ having ~~a same set of substantially similar~~ registration points into ~~a same corresponding the common~~ location of said composite image.

9. (Cancelled)

10. (Currently Amended): The method according to claim 4, wherein ~~said step of performing a transformation comprises:~~ includes applying a predetermined bilinear transformation matrix to each patch, said predetermined bilinear transformation matrix representing an amount of warping required for each patch to transform each patch into said common coordinate system.

11. (Currently Amended): ~~The A method of claim 7, comprising:~~
synchronously capturing a set of images from a camera array;
selecting pixels from at least one image from the set of images;
identifying contiguous patches from the selected pixels;
transforming the selected pixels from a coordinate system of the at least one image to a common coordinate system;
determining overlap between the contiguous patches, wherein overlapping contiguous patches include pixels having substantially similar registration points;
combining overlapping contiguous patches into a common location of said composite image;
wherein combining overlapping contiguous patches includes cross-fading pixels having substantially similar registration points into the common location of said composite image;
wherein ~~said step of cross-fading comprises the steps of:~~ includes:
varying a parameter of ~~each pixel of the pixels having substantially similar registration points from~~ a first patch from a minimum value at a first boundary of said first patch to a maximum value at an opposite boundary of said first patch;

varying said parameter of ~~each pixel of the pixels having substantially similar registration points from~~ a second patch from said maximum value at a boundary of said second patch corresponding to said first boundary to said minimum value at a boundary of said second patch corresponding to said opposite boundary;

summing ~~each of~~ corresponding pixel values of ~~each~~ said first patch and said second patch; and

placing the summed values in corresponding locations of said common coordinate system.

12. (Original): The method according to claim 11, wherein said parameter is at least one of brightness, contrast, and intensity.

13. (Currently Amended): The method according to claim 1, further comprising ~~the step of:~~ repeating said ~~step of~~ applying a transformative equation for each set of images synchronously captured by said camera array, each set of images representing one frame in a video stream of said scene.

14. (Currently Amended): The method according to claim 1, further comprising ~~the steps of:~~ selecting an area of interest from the composite image; and outputting the selected area of interest to a user.

15. (Currently Amended): The method according to claim 14, wherein said ~~step of~~ outputting comprises ~~the step of~~ displaying said area of interest from the combined warped images.

16. (Currently Amended): The method according to claim 14, wherein said ~~step of~~ selecting comprises:

directing said area of interest to a predetermined area surrounding at least one of motion detected in said scene, audio sources detected within said scene, and proximity of objects detected in said scene.

17. (Withdrawn): A method of controlling a virtual camera having a view selected from an array of cameras, comprising the steps of:

combining images from each of said cameras into a panoramic view;
detecting motion in said panoramic view; and
directing a view of said virtual camera based on said motion.

18. (Withdrawn): The method according to claim 17, wherein:
said method further comprises the step of:
ranging objects in said panoramic view by stereoscopically calculating a range of said objects; and
said step of directing comprises directing a view of said virtual camera based on the motion detected
and a range of said objects.

19. (Withdrawn): The method according to claim 18, wherein:
said method further comprises the steps of:
retrieving audio inputs from a set of directive microphones, and
determining a direction of said audio inputs within said panoramic view; and
said step of directing comprises directing a view of said virtual camera based on at least one of said
motion, a range of said objects, and a direction of said audio inputs.

20. (Currently Amended): A camera array, comprising:
a set of cameras mounted in an array;
a set of camera offset values for the set of cameras;
an image combining mechanism configured to combine at least two of images captured from said set
of cameras into a composite image, the image combining mechanism including:
a warping device configured to warp patches of each image into a common coordinate
system of said composite image by applying a bilinear transformation;
wherein the warping device applies the set of camera offset values to warp patches;
a view selection device configured to select a view from the composite image; and
an output mechanism configured to display the selected view.

21. (Previously Presented): The camera array according to claim 20, wherein said image
combining mechanism includes,

a fading device configured to fade and combine patches having a same location in said composite image.

22. (Previously Presented): The camera array according to claim 20, wherein said view selection device includes:

at least one of,

a video motion detector configured to detect motion in the composite image,

a sound detection device configured to determine a location of sound originating within said composite image, and

a stereoscopic ranging mechanism configured to utilize at least two images from separate cameras of said camera array to determine a range of objects in said composite image; and

a detection mechanism configured to automatically detect any of a face, shape, color, and motion of a subject for inclusion in said selected frame based on at least one of ranging data from said stereoscopic ranging mechanism, location data from said sound detection device, and motion detected by said video motion detector.

23. (Original): The camera array according to claim 21, wherein:

said array of cameras are immovably mounted on a firm fixed base; and

said warping device applies a pre-determined transformation to each of said patches.

24. (Original): The camera array according to claim 21, further comprising a registration mechanism configured to register each of said camera arrays by finding registration points in common with views of each camera and said composite image.

25. (Currently Amended): ~~The A~~ camera array according to claim 24, wherein said registration device, comprising comprises:

a plurality of cameras;

an image combining mechanism configured to combine at least two images captured from said plurality of cameras into a composite image, the image combining mechanism including:

a registration mechanism configured to register said plurality of cameras by finding registration points in common with views of the plurality of cameras and said composite image, the registration mechanism including:

a registration point source directable to locations within said views of the plurality of cameras, ~~each camera view~~; and

a detection mechanism configured to detect said registration point source and register the detected registration point source in said views of the plurality of cameras ~~each of said camera views~~ with respect to a coordinate system of said composite image.

26. (Original): The camera array according to claim 25, wherein said registration point source is at least one of a light source directed into view of said camera array and a grid placed in view of said camera array.

27. (Cancelled)

28. (Previously Presented): The method according to claim 30, wherein said step placing comprises the steps of:

sweeping an beam light source across a field of view of at least two cameras of said camera array.

29. (Previously Presented): The method according to claim 30, wherein said step of placing comprises the step of:

placing a grid of known location in a field of view in at least two cameras of said array.

30. (Previously Presented): A method of registering a camera array, comprising:
placing at least one registration point in a field of view of at least two cameras of said camera array;
identifying a location of each registration point in a field of view of each camera of said array;
calculating a warped coordinate system for placing pixels of said cameras; and
maintaining a table identifying pixels of said cameras, an amount of fade, and a corresponding location in the warped coordinate system such that images can be combined in relation to said registration points.

31. (Currently Amended): A method, comprising:
providing a camera array, the camera array including a plurality of cameras;
providing a set of camera offset values for the camera array;
synchronously capturing a set of images from [a] the camera array;
selecting pixels from at least one image of said set of images; and
applying a transformative equation to the selected pixels to transform the selected pixels from a coordinate system of the at least one image to a common coordinate system of a composite image;
wherein said transformative equation is at least one of a bilinear transformation, a radial transformation, and an affine transformation;
wherein applying a transformative equation includes using the set of camera offset values.